



AM18

channel nut, A7/A8

galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

| Product | Ø | t | G |
|----------|-------|---------|------------|
| AM18 M6 | 6 mm | 6,00 mm | 2,6 kg/100 |
| AM18 M8 | 8 mm | 6,00 mm | 2,4 kg/100 |
| AM18 M10 | 10 mm | 8,00 mm | 3,3 kg/100 |
| AM18 M12 | 12 mm | 9,50 mm | 4,2 kg/100 |

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product | Ø | t | G |
|-----------|-------|---------|------------|
| AM18 M6F | 6 mm | 6,00 mm | 2,8 kg/100 |
| AM18 M8F | 8 mm | 6,00 mm | 2,6 kg/100 |
| AM18 M10F | 10 mm | 8,00 mm | 3,5 kg/100 |
| AM18 M12F | 12 mm | 9,50 mm | 4,5 kg/100 |

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Product | Ø | t | G |
|------------|-------|---------|------------|
| AM18 M6E4 | 6 mm | 6,00 mm | 3 kg/100 |
| AM18 M8E4 | 8 mm | 6,00 mm | 2,9 kg/100 |
| AM18 M10E4 | 10 mm | 8,00 mm | 3,6 kg/100 |
| AM18 M12E4 | 12 mm | 9,50 mm | 3,4 kg/100 |

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product | Ø | t | G |
|-------------|------|---------|-------------|
| AM18 M6-HDG | 6 mm | 6,00 mm | 2,70 kg/100 |



| Product | Ø | t | G |
|--------------|-------|---------|-------------|
| AM18 M8-HDG | 8 mm | 6,00 mm | 2,60 kg/100 |
| AM18 M10-HDG | 10 mm | 8,00 mm | 3,20 kg/100 |
| AM18 M12-HDG | 12 mm | 9,50 mm | 3,50 kg/100 |

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Product | Ø | t | G |
|-------------|------|---------|-------------|
| AM18 M6-316 | 6 mm | 6,00 mm | 2,70 kg/100 |

Ø: diameter
t: material thickness
G: weight

DETAILS / APPLICATIONS

