



KTW-A 4-12

cable support trough, Ø 40-120 mm

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	D	G
KTW-A 4	56 mm	40 mm	0,3 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		
KTW-A 5	66 mm	50 mm	0,32 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		
KTW-A 6	76 mm	60 mm	0,35 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		
KTW-A 7	86 mm	70 mm	0,39 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		
KTW-A 8	96 mm	80 mm	0,44 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		
KTW-A 10	118 mm	100 mm	0,48 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		



Product	B	D	G
KTW-A 12	138 mm	120 mm	0,55 kg
incl.:			
1x IK 8X16E	hexagon socket head screw, DIN 912		
1x AMA18 M8F	channel nut, A 7/A 8/A 9		

B: width
D: diameter
G: weight

DETAILS / APPLICATIONS

