


## LADR

cable ladder branch cover with turning bolts

Cover for branch.



### Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	B	R	t	G
LADR 20S	204 mm	398 mm	0,75 mm	2,73 kg
LADR 30S	304 mm	398 mm	1,00 mm	5,20 kg
LADR 40S	404 mm	398 mm	1,00 mm	6,99 kg
LADR 50S	504 mm	398 mm	1,25 mm	11,11 kg
LADR 60S	604 mm	398 mm	1,25 mm	13,74 kg

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	R	t	G
LADR 20F	204 mm	398 mm	0,75 mm	2,91 kg
LADR 30F	304 mm	398 mm	1,00 mm	5,56 kg
LADR 40F	404 mm	398 mm	1,00 mm	7,47 kg
LADR 50F	504 mm	398 mm	1,25 mm	11,89 kg
LADR 60F	604 mm	398 mm	1,25 mm	14,70 kg

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	R	t	G
LADR 20E	204 mm	398 mm	0,80 mm	2,91 kg



Product	B	R	t	G
LADR 30E	304 mm	398 mm	1,00 mm	5,23 kg
LADR 40E	404 mm	398 mm	1,00 mm	7,03 kg
LADR 50E	504 mm	398 mm	1,25 mm	11,18 kg
LADR 60E	604 mm	398 mm	1,25 mm	13,83 kg

**B:** width  
**R:** radius  
**t:** material thickness  
**G:** weight

## DETAILS / APPLICATIONS

