



LK ND K

cable holder, plastic, with nail plug

flame-resistant according to specification of UL94 V-0 and fire hazard testing VDE 0471/DIN IEC 695 part 2-1, testing temperature T_{max}

Suitable for applications with low installation height. The information on the number of cables relating to the use of NYM cable (3 x 1.5 mm²).

Polyamide

Product	H	number of cables	color	G	PT
LK 8 ND K	16 mm	8	RAL 7035	0,02 kg	750 °C
incl.: 1x SN 6X50 screw nail anchor					
LK 10 ND K	16 mm	10	RAL 7035	0,02 kg	750 °C
incl.: 1x SN 6X50 screw nail anchor					
LK 16 ND K	16 mm	16	RAL 7035	0,03 kg	750 °C
incl.: 1x SN 6X50 screw nail anchor					
LK 8 ND FWK	16 mm	8	RAL 7030	0,02 kg	960 °C
incl.: 1x SN 6X50 screw nail anchor					
LK 10 ND FWK	16 mm	10	RAL 7030	0,02 kg	960 °C
incl.: 1x SN 6X50 screw nail anchor					
LK 16 ND FWK	16 mm	16	RAL 7030	0,03 kg	960 °C
incl.: 1x SN 6X50 screw nail anchor					

H: height

number of cables: Maximum number of installable cables

color:





G: weight
PT: test temperature

