



RDR

cable tray cover with turning bolts

cable tray cover, positive locking, with additional turning bolts

Installation of covers in outdoor areas requires additional provisions against storm forces. Turning bolts are in no case sufficient as security provision. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish.

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

| Product | B | L | G |
|---------|--------|---------|---------|
| RDR 05S | 50 mm | 3000 mm | 1,65 kg |
| RDR 10S | 100 mm | 3000 mm | 2,3 kg |
| RDR 20S | 200 mm | 3000 mm | 4,1 kg |
| RDR 30S | 300 mm | 3000 mm | 7,8 kg |
| RDR 40S | 400 mm | 3000 mm | 10,1 kg |
| RDR 50S | 500 mm | 3000 mm | 15,6 kg |
| RDR 60S | 600 mm | 3000 mm | 18,5 kg |

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product | B | L | G |
|---------|--------|---------|---------|
| RDR 05F | 50 mm | 3000 mm | 1,70 kg |
| RDR 10F | 100 mm | 3000 mm | 2,8 kg |
| RDR 20F | 200 mm | 3000 mm | 4,7 kg |
| RDR 30F | 300 mm | 3000 mm | 7,9 kg |
| RDR 40F | 400 mm | 3000 mm | 11,4 kg |
| RDR 50F | 500 mm | 3000 mm | 17,4 kg |
| RDR 60F | 600 mm | 3000 mm | 20,6 kg |



Stainless steel, according to ASTM 304 / BS 304 S 3

| Product | B | L | G |
|---------|--------|---------|---------|
| RDR 05E | 50 mm | 3000 mm | 1,65 kg |
| RDR 10E | 100 mm | 3000 mm | 2,6 kg |
| RDR 20E | 200 mm | 3000 mm | 4,5 kg |
| RDR 30E | 300 mm | 3000 mm | 7,9 kg |
| RDR 40E | 400 mm | 3000 mm | 10,3 kg |
| RDR 50E | 500 mm | 3000 mm | 15,2 kg |
| RDR 60E | 600 mm | 3000 mm | 18 kg |

B: width
L: length
G: weight

DETAILS / APPLICATIONS

