



## RDS

cable tray, heavy

cable tray cover, heavy, positive locking

### Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

| Product | B      | L       | t       | G        |
|---------|--------|---------|---------|----------|
| RDS 05S | 50 mm  | 3000 mm | 1,50 mm | 3,03 kg  |
| RDS 10S | 100 mm | 3000 mm | 1,50 mm | 4,80 kg  |
| RDS 20S | 200 mm | 3000 mm | 1,50 mm | 8,33 kg  |
| RDS 30S | 300 mm | 3000 mm | 1,50 mm | 11,87 kg |
| RDS 40S | 400 mm | 3000 mm | 1,50 mm | 15,40 kg |
| RDS 50S | 500 mm | 3000 mm | 1,50 mm | 18,93 kg |
| RDS 60S | 600 mm | 3000 mm | 1,50 mm | 22,46 kg |

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product | B      | L       | t       | G        |
|---------|--------|---------|---------|----------|
| RDS 05F | 50 mm  | 3000 mm | 1,50 mm | 3,10 kg  |
| RDS 10F | 100 mm | 3000 mm | 1,50 mm | 5,14 kg  |
| RDS 20F | 200 mm | 3000 mm | 1,50 mm | 8,92 kg  |
| RDS 30F | 300 mm | 3000 mm | 1,50 mm | 12,70 kg |
| RDS 40F | 400 mm | 3000 mm | 1,50 mm | 16,47 kg |
| RDS 50F | 500 mm | 3000 mm | 1,50 mm | 20,25 kg |
| RDS 60F | 600 mm | 3000 mm | 1,50 mm | 24,03 kg |



**B:** width  
**L:** length  
**t:** material thickness  
**G:** weight

## DETAILS / APPLICATIONS

