



RID

cable installation tray cover

positive locking cable installation tray cover

Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

Product	B	L	G
RID 05S	50 mm	3000 mm	1,52 kg
RID 10S	100 mm	3000 mm	2,40 kg
RID 15S	150 mm	3000 mm	3,29 kg
RID 20S	200 mm	3000 mm	4,17 kg
RID 30S	300 mm	3000 mm	7,91 kg

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	L	G
RID 05F	50 mm	3000 mm	1,63 kg
RID 10F	100 mm	3000 mm	2,57 kg
RID 15F	150 mm	3000 mm	3,52 kg
RID 20F	200 mm	3000 mm	4,46 kg
RID 30F	300 mm	3000 mm	8,47 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	L	G
RID 05E	50 mm	3000 mm	1,63 kg



Product	B	L	G
RID 10E	100 mm	3000 mm	2,58 kg
RID 15E	150 mm	3000 mm	3,53 kg
RID 20E	200 mm	3000 mm	4,47 kg
RID 30E	300 mm	3000 mm	7,96 kg

B: width
L: length
G: weight

DETAILS / APPLICATIONS

