


SEMS

hexagon-nut with flange, DIN EN 1661



galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

Product	D	Ø	t	SW	G
SEMS 6	14 mm	6 mm	5,50 mm	10 mm	0,3 kg/100
SEMS 8	17 mm	8 mm	7,50 mm	13 mm	0,7 kg/100
SEMS 10	21 mm	10 mm	9,50 mm	15 mm	1,0 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	D	Ø	t	SW	G
SEMS 6E	14 mm	6 mm	5,50 mm	10 mm	0,3 kg/100
SEMS 8E	17 mm	8 mm	7,50 mm	13 mm	0,7 kg/100

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	D	Ø	t	SW	G
SEMS 6-304	14 mm	6 mm	5,50 mm	10 mm	0,30 kg/100
SEMS 8-304	17 mm	8 mm	7,50 mm	13 mm	0,7 kg/100
SEMS 10-304	21 mm	10 mm	9,50 mm	15 mm	1,0 kg/100

D: diameter



Ø: diameter
t: material thickness
SW: wrench size
G: weight

DETAILS / APPLICATIONS

