



SRB 90
tube bow, 90°

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	D	R	t	G
SRB 90-60F	225 mm	100 mm	60 mm	150 mm	2,00 mm	1,3 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	D	R	t	G
SRB 90-60E	225 mm	100 mm	60 mm	150 mm	2,00 mm	1,3 kg

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	D	R	t	G
SRB 90-30-HDG	185 mm	100 mm	30 mm	140 mm	1,50 mm	0,40 kg
SRB 90-60-HDG	185 mm	100 mm	60 mm	150 mm	2,00 mm	1,30 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	D	R	t	G
SRB 90-30-304	185 mm	100 mm	30 mm	140 mm	1,50 mm	0,4 kg
SRB 90-60-304	185 mm	100 mm	60 mm	150 mm	2,00 mm	1,3 kg



Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	D	R	t	G
SRB 90-30-316	185 mm	100 mm	30 mm	140 mm	1,50 mm	0,4 kg
SRB 90-60-316	185 mm	100 mm	60 mm	150 mm	2,00 mm	1,3 kg

H: height
B: width
D: diameter
R: radius
t: material thickness
G: weight

DETAILS / APPLICATIONS

