



SRF
floor fastening system

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	L	D	t	G
SRF 60F	230 mm	80 mm	220 mm	60 mm	2,50 mm	1,75 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	L	D	t	G
SRF 60E	230 mm	80 mm	220 mm	60 mm	2,50 mm	1,75 kg

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	L	D	t	G
SRF 30-HDG	130 mm	40 mm	130 mm	31 mm	1,50 mm	0,28 kg
SRF 60-HDG	230 mm	40 mm	220 mm	61 mm	2,50 mm	1,75 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	L	D	t	G
SRF 30-304	130 mm	40 mm	130 mm	31 mm	1,50 mm	0,28 kg
SRF 60-304	230 mm	40 mm	220 mm	61 mm	2,50 mm	1,75 kg



Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	L	D	t	G
SRF 30-316	130 mm	40 mm	130 mm	31 mm	1,50 mm	0,28 kg
SRF 60-316	230 mm	40 mm	220 mm	61 mm	2,50 mm	1,75 kg

H: height
B: width
L: length
D: diameter
t: material thickness
G: weight

DETAILS / APPLICATIONS

