



# STU 50-3E

vertical cable ladder, equal U-profile

vertical ladder, medium building class, with continuously perforated side beams, for fastening directly to walls, riveted rungs made of profile rails 40x22 mm to be screwed in.

Beams and rungs are delivered not mounted including screws and nuts. This article is available made in material No. 1.4571/1.4404 (V4A) stainless steel finish. The cover RD can only be mounted in conjunction with the cover extension STD-A.

**Stainless steel, according to ASTM 304 / BS 304 S 3**

Product	H	B1	B2	L	t	P <sub>max</sub>	G
STU 50-03-3E	50 mm	300 mm	156 mm	3000 mm	2 mm	2,0 kN	10,9 kg
incl.: 2x KHU 50-30E 5x STUS 50-03E bracket support, 50x22 mm rung							
STU 50-04-3E	50 mm	400 mm	356 mm	3000 mm	2 mm	2,0 kN	11,4 kg
incl.: 2x KHU 50-30E 5x STUS 50-04E bracket support, 50x22 mm rung							
STU 50-05-3E	50 mm	500 mm	456 mm	3000 mm	2 mm	2,0 kN	11,9 kg
incl.: 2x KHU 50-30E 5x STUS 50-05E bracket support, 50x22 mm rung							
STU 50-06-3E	50 mm	600 mm	556 mm	3000 mm	2 mm	2,0 kN	12,4 kg
incl.: 2x KHU 50-30E 5x STUS 50-06E bracket support, 50x22 mm rung							
STU 50-07-3E	50 mm	700 mm	656 mm	3000 mm	2 mm	2,0 kN	12,9 kg
incl.: 2x KHU 50-30E 5x STUS 50-07E bracket support, 50x22 mm rung							
STU 50-08-3E	50 mm	800 mm	756 mm	3000 mm	2 mm	2,0 kN	13,5 kg
incl.: 2x KHU 50-30E 5x STUS 50-08E bracket support, 50x22 mm rung							





Product	H	B1	B2	L	t	P <sub>max</sub>	G
STU 50-02-3E	3000 mm	2,0 kN	10,4 kg				
incl.:							
2x KHU 50-30E		bracket support, 50x22 mm					
5x STUS 50-02E		rung					

**H:** height  
**B1:** width  
**B2:** width  
**L:** length  
**t:** material thickness  
**P<sub>max</sub>:** Maximum load  
**G:** weight

## OPTIONAL ACCESSORIES

AC, LGV 50, STR 50, STR 110, STD-A, ST-RD, BL 4, LH

