


UKE185 V

stainless steel hinged cover compact single-outlet, octuple, angular



Consisting of floor box inclusive square single outlet and shuttering formwork, as concealed shuttering for direct installation in floor screed. as a height-adjustable cartridge installation frame with cable outlet cartridge, hem, self-locking opening lever, floor-flush cable outlet and rubber seal to accommodate up to eight installation devices, 45x45mm With perforations on the side panels for the introduction of tubes M25. Suitable for rooms with dry and damp-cleaned floor covers. Designed for office traffic loads.



norm	according to DIN EN 50085
permits	according to VDE / TÜV


Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	H _{min}	N	B	L	E	T	P _{max}	IP _n	IP _g	G
UKE185 15-V E	15 mm	90 mm	35 mm	184 mm	258 mm	190 x 264 mm	12 mm	2 kN	IP 30	IP 20	3,28 kg
UKE185 25-V E	25 mm	100 mm	35 mm	184 mm	258 mm	190 x 264 mm	22 mm	2 kN	IP 30	IP 20	3,65 kg

H: height
H_{min}: Minimum installation height
N: levelling range
B: width
L: length
E: fitting dimension
T: depth
P_{max}: Maximum load
IP_n: IP protection level in unused condition
IP_g: IP protection level in used condition
G: weight



DETAILS / APPLICATIONS



OPTIONAL ACCESSORIES

UG3, UKENP 185



dry-cleaned

