


# UST45 1

shockproof socket, single

One-piece latchable single isolated ground receptacle, 45x45 mm design made of plastic with 33° or 0° plugging angle, push terminals, increased contact protection according to VDE 0620 and nominal voltage/- current: AC 250 V, 10/16 A.



**Polycarbonate**

Product	H	B	L	color	plug angle	G
UST45-W 1	42 mm	40 mm	45 mm	white (similar to RAL 9010)	33 °	0,04 kg
UST45-R 1	42 mm	40 mm	45 mm	red (similar to RAL 3003)	33 °	0,04 kg
UST45-O 1	42 mm	40 mm	45 mm	orange (similar to RAL 2004)	33 °	0,04 kg
UST45-G 1	42 mm	40 mm	45 mm	green (similar to RAL 6029)	33 °	0,04 kg
UST45-W 01	42 mm	40 mm	45 mm	white (similar to RAL 9010)	-	0,04 kg
UST45-R 01	42 mm	40 mm	45 mm	red (similar to RAL 3003)	-	0,04 kg
UST45-O 01	42 mm	40 mm	45 mm	orange (similar to RAL 2004)	-	0,04 kg
UST45-G 01	42 mm	40 mm	45 mm	green (similar to RAL 6029)	-	0,04 kg
UST45-S 01	42 mm	40 mm	45 mm	Black (similar to RAL 7021)	-	0,04 kg

**H:** height  
**B:** width  
**L:** length  
**color:**  
**plug angle:**  
**G:** weight

## OPTIONAL ACCESSORIES

UAM 1

