



WPIR 100

wide-span inside riser, height = 100 mm

wide-span cable ladder bend 90° for vertical change of direction with integrated connectors

Welded construction. Formed components must be supported at all sides. The following angles are available on request: 30 °, 45 °, 60 °. The following radii are available on request: 300 mm, 600 mm, 900 mm.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	angle	R	G
WPIR10-20-90-45-HDG	100 mm	200 mm	90 °	450 mm	7,45 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-30-90-45-HDG	100 mm	300 mm	90 °	450 mm	8,09 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-40-90-45-HDG	100 mm	400 mm	90 °	450 mm	8,72 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-45-90-45-HDG	100 mm	450 mm	90 °	450 mm	9,04 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-50-90-45-HDG	100 mm	500 mm	90 °	450 mm	9,36 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-60-90-45-HDG	100 mm	600 mm	90 °	450 mm	10,00 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-70-90-45-HDG	100 mm	700 mm	90 °	450 mm	10,63 kg
incl.: 8x KLS 10X20-HDG				clamp fastening set	
WPIR10-75-90-45-HDG	100 mm	750 mm	90 °	450 mm	10,95 kg





Product	H	B	angle	R	G
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPIR10-80-90-45-HDG	100 mm	800 mm	90 °	450 mm	11,27 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPIR10-90-90-45-HDG	100 mm	900 mm	90 °	450 mm	11,90 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPIR10-100-90-45-HDG	100 mm	1000 mm	90 °	450 mm	12,54 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	angle	R	G
WPIR10-20-90-45-304	100 mm	200 mm	90 °	450 mm	7,45 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-30-90-45-304	100 mm	300 mm	90 °	450 mm	8,09 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-40-90-45-304	100 mm	400 mm	90 °	450 mm	8,72 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-45-90-45-304	100 mm	450 mm	90 °	450 mm	9,04 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-50-90-45-304	100 mm	500 mm	90 °	450 mm	9,36 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-60-90-45-304	100 mm	600 mm	90 °	450 mm	10,00 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-70-90-45-304	100 mm	700 mm	90 °	450 mm	10,63 kg





Product	H	B	angle	R	G
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-75-90-45-304	100 mm	750 mm	90 °	450 mm	10,95 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-80-90-45-304	100 mm	800 mm	90 °	450 mm	11,27 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-90-90-45-304	100 mm	900 mm	90 °	450 mm	11,90 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPIR10-100-90-45-304	100 mm	1000 mm	90 °	450 mm	12,54 kg
incl.: 8x KLS 10X20-304					clamp fastening set

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	angle	R	G
WPIR10-20-90-45-316	100 mm	200 mm	90 °	450 mm	7,45 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPIR10-30-90-45-316	100 mm	300 mm	90 °	450 mm	8,09 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPIR10-40-90-45-316	100 mm	400 mm	90 °	450 mm	8,72 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPIR10-45-90-45-316	100 mm	450 mm	90 °	450 mm	9,04 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPIR10-50-90-45-316	100 mm	500 mm	90 °	450 mm	9,36 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPIR10-60-90-45-316	100 mm	600 mm	90 °	450 mm	10,00 kg



Product	H	B	angle	R	G
incl.: 8x KLS 10X20-316					
clamp fastening set					
WPIR10-70-90-45-316	100 mm	700 mm	90 °	450 mm	10,63 kg
incl.: 8x KLS 10X20-316					
clamp fastening set					
WPIR10-75-90-45-316	100 mm	750 mm	90 °	450 mm	10,95 kg
incl.: 8x KLS 10X20-316					
clamp fastening set					
WPIR10-80-90-45-316	100 mm	800 mm	90 °	450 mm	11,27 kg
incl.: 8x KLS 10X20-316					
clamp fastening set					
WPIR10-90-90-45-316	100 mm	900 mm	90 °	450 mm	11,90 kg
incl.: 8x KLS 10X20-316					
clamp fastening set					
WPIR10-100-90-45-316	100 mm	1000 mm	90 °	450 mm	12,54 kg
incl.: 8x KLS 10X20-316					
clamp fastening set					

H: height
B: width
angle: angle
R: radius
G: weight

DETAILS / APPLICATIONS



