



WPLEAB 150

wide-span ladder bend

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	G
WPLEAB 150F	150 mm	9,45 kg
incl.:		
16x FRSV 10X20F		round-head screw with short square, DIN 603
16x SEM 10F		hexagon-nut, DIN 934
8x FRS 6X25E		round-head screw with square, DIN 603
8x SEM 6E		hexagon-nut, DIN 934
1x KHA 8-08F		profile rail 40x22 mm, perforated
3x FKS 6X20E		slotted cylinder head screw, DIN EN ISO 1580
2x AMA18 M6F		channel nut, A 7/A 8/A 9
1x AMF18 M6F		channel spring nut, A7/A8

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	G
WPLEAB 150E	150 mm	8,55 kg
incl.:		
16x FRSV 10X20E		round-head screw with short square, DIN 603
16x SEMS 10E		hexagon-nut with flange, DIN EN 1661
8x FRS 6X25E		round-head screw with square, DIN 603
8x SEM 6E		hexagon-nut, DIN 934
1x KHA 7-08E		profile rail 39.5x22 mm, perforated
3x FKS 6X20E		slotted cylinder head screw, DIN EN ISO 1580
3x AMA18 M6E		channel nut, A 7/A 8/A 9





H: height
G: weight

