



WPOR 60

wide-span outside riser, height = 60 mm

wide-span cable ladder outside raiser 90° for vertical change of direction with integrated connectors

Welded construction. Formed components must be supported at all sides.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	angle	R	G
WPOR06-15-90-30-HDG	60 mm	150 mm	90 °	300 mm	3,88 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR06-20-90-30-HDG	60 mm	200 mm	90 °	300 mm	4,19 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR06-30-90-30-HDG	60 mm	300 mm	90 °	300 mm	4,67 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR06-40-90-30-HDG	60 mm	400 mm	90 °	300 mm	5,15 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR06-60-90-30-HDG	60 mm	600 mm	90 °	300 mm	6,10 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					

H: height
B: width
angle: angle
R: radius
G: weight



DETAILS / APPLICATIONS

