



## AMF22

glijmoer met veer, A41, KHA 41, KHAL 41

### Verzinkt volgens DIN EN ISO 19598 / DIN EN ISO 2081

Product	Ø	t	G
AMF22 M6	6 mm	6,00 mm	2,8 kg/100
AMF22 M8	8 mm	6,00 mm	2,6 kg/100
AMF22 M10	10 mm	8,00 mm	3,5 kg/100
AMF22 M12	12 mm	9,50 mm	4,4 kg/100

### Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	Ø	t	G
AMF22 M6F	6 mm	6,00 mm	3 kg/100
AMF22 M8F	8 mm	6,00 mm	2,8 kg/100
AMF22 M10F	10 mm	8,00 mm	4,0 kg/100
AMF22 M12F	12 mm	9,50 mm	4,4 kg/100

### Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	Ø	t	G
AMF22 M6E4	6 mm	6,00 mm	2,7 kg/100
AMF22 M8E4	8 mm	6,00 mm	2,9 kg/100
AMF22 M10E4	10 mm	8,00 mm	3,5 kg/100





Product	Ø	t	G
AMF22 M12E4	12 mm	9,50 mm	3,5 kg/100

## Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	Ø	t	G
AMF22 M6-HDG	6 mm	6,00 mm	2,90 kg/100
AMF22 M8-HDG	8 mm	6,00 mm	2,90 kg/100
AMF22 M10-HDG	10 mm	8,00 mm	4,0 kg/100
AMF22 M12-HDG	12 mm	9,50 mm	4,4 kg/100

## Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	Ø	t	G
AMF22 M6-316	6 mm	6,00 mm	3 kg/100
AMF22 M8-316	8 mm	6,00 mm	2,8 kg/100
AMF22 M10-316	10 mm	8,00 mm	3,7 kg/100
AMF22 M12-316	12 mm	9,50 mm	4,0 kg/100

Ø: diameter  
t: materiaaldikte  
G: gewicht

## DETAILS / TOEPASSINGEN



