



GID draadgoot deksel

Continu thermisch verzinkt (Senzimir-techniek) (DIN EN 10346)

| Product | B | L | G |
|---------|--------|---------|----------|
| GID 12S | 120 mm | 3000 mm | 4,66 kg |
| GID 20S | 200 mm | 3000 mm | 6,55 kg |
| GID 30S | 300 mm | 3000 mm | 8,91 kg |
| GID 40S | 400 mm | 3000 mm | 11,30 kg |
| GID 50S | 500 mm | 3000 mm | 13,62 kg |
| GID 60S | 600 mm | 3000 mm | 19,98 kg |
| GID 06S | 60 mm | 3000 mm | 3,53 kg |

Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

| Product | B | L | G |
|---------|--------|---------|----------|
| GID 12F | 120 mm | 3000 mm | 4,99 kg |
| GID 20F | 200 mm | 3000 mm | 7,00 kg |
| GID 30F | 300 mm | 3000 mm | 9,53 kg |
| GID 40F | 400 mm | 3000 mm | 12,09 kg |
| GID 50F | 500 mm | 3000 mm | 14,57 kg |
| GID 60F | 600 mm | 3000 mm | 21,05 kg |
| GID 06F | 60 mm | 3000 mm | 3,47 kg |



Roestvrij staal, volgens ASTM 304 / BS 304 S 3

| Product | B | L | G |
|---------|--------|---------|----------|
| GID 12E | 120 mm | 3000 mm | 4,69 kg |
| GID 20E | 200 mm | 3000 mm | 6,59 kg |
| GID 30E | 300 mm | 3000 mm | 8,96 kg |
| GID 40E | 400 mm | 3000 mm | 11,33 kg |
| GID 50E | 500 mm | 3000 mm | 13,71 kg |
| GID 60E | 600 mm | 3000 mm | 20,11 kg |
| GID 06E | 60 mm | 3000 mm | 3,56 kg |

B: breedte
L: lengte
G: gewicht

DETAILS / TOEPASSINGEN

