


RBVD

kabelgoot bochtdeksel, variabel

kabelgoot bochtdeksel, sluitend passend



Continu thermisch verzinkt (Senzimir-techniek) (DIN EN 10346)

Product	B	G
RBVD 05S	50 mm	0,05 kg
RBVD 10S	100 mm	0,13 kg
RBVD 20S	200 mm	0,38 kg
RBVD 30S	300 mm	0,75 kg
RBVD 40S	400 mm	1,24 kg
RBVD 50S	500 mm	1,86 kg
RBVD 60S	600 mm	2,60 kg

Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	B	G
RBVD 05E	50 mm	0,05 kg
RBVD 10E	100 mm	0,13 kg
RBVD 20E	200 mm	0,38 kg
RBVD 30E	300 mm	0,76 kg
RBVD 40E	400 mm	1,27 kg
RBVD 50E	500 mm	1,90 kg
RBVD 60E	600 mm	2,65 kg





Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	B	G
RBVD 05E4	50 mm	0,05 kg
RBVD 10E4	100 mm	0,13 kg
RBVD 20E4	200 mm	0,38 kg
RBVD 30E4	300 mm	0,76 kg
RBVD 40E4	400 mm	1,27 kg
RBVD 50E4	500 mm	1,90 kg
RBVD 60E4	600 mm	2,65 kg

B: breedte
G: gewicht

