



SRHD

Beschermbuishouder, draaibaar

Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	H	B	L	D	t	G
SRHD 60F	102 mm	1,5 mm	115 mm	60 mm	2,00 mm	1,2 kg

Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	H	B	L	D	t	G
SRHD 30-HDG	62 mm	1,5 mm	80 mm	30 mm	1,50 mm	0,70 kg
SRHD 60-HDG	102 mm	1,5 mm	115 mm	60 mm	2,00 mm	1,20 kg

Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	H	B	L	D	t	G
SRHD 30-304	62 mm	1,5 mm	80 mm	30 mm	1,50 mm	0,7 kg
SRHD 60-304	102 mm	1,5 mm	115 mm	60 mm	2,00 mm	1,2 kg

Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	L	D	t	G
SRHD 30-316	62 mm	1,5 mm	80 mm	30 mm	1,50 mm	0,7 kg



Product	H	B	L	D	t	G
SRHD 60-316	102 mm	1,5 mm	115 mm	60 mm	2,00 mm	1,2 kg

Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	H	B	L	D	t	G
SRHD 30E	62 mm	1,5 mm	80 mm	30 mm	1,50 mm	0,7 kg
SRHD 60E	102 mm	1,5 mm	115 mm	60 mm	2,00 mm	1,2 kg

H: hoogte

B: breedte

L: lengte

D: diameter

t: materiaaldikte

G: gewicht

DETAILS / TOEPASSINGEN

