



## SRS-B

buisklem U beugel

### Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	D	t	G
SRS-B 60-10F	60 mm	10,00 mm	0,06 kg

### Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	D	t	G
SRS-B 30-6E	31 mm	6,00 mm	0,03 kg
SRS-B 60-8E	61 mm	8,00 mm	0,22 kg

### Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	D	t	G
SRS-B 60-10-HDG	61 mm	10,00 mm	0,11 kg

### Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	D	t	G
SRS-B 30-6-304	31 mm	6,00 mm	0,03 kg
SRS-B 60-8-304	61 mm	8,00 mm	0,11 kg





## Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	D	t	G
SRS-B 30-6-316	31 mm	6,00 mm	0,03 kg
SRS-B 60-8-316	61 mm	8,00 mm	0,22 kg

**D:** diameter

**t:** materiaaldikte

**G:** gewicht

